


| SPECIFICATION | CONNECTION | BIPOLAR |
|--|------------|------------------------------|
| AMPS/PHASE | | 0.67 |
| RESISTANCE/PHASE(Ohms)@25°C | | 5.60±10% |
| INDUCTANCE/PHASE(mH)@1KHz | | 4.00±20% |
| HOLDING TORQUE w/o GEARBOX(Nm)[lb-in] | | 0.07[0.62] |
| GEAR RATIO | | 5 ₁₁ ² |
| EFFICIENCY | | 90.00% |
| STEP ANGLE w/o GEARBOX(°) | | 1.80 |
| BACKLASH@NO-LOAD | | <=1° |
| MAX.PERMISSIBLE TORQUE(Nm) | | 2.00 |
| MOMENT PERMISSIBLE TORQUE(Nm) | | 4.00 |
| SHAFT MAXIMUM AXIAL LOAD(N) | | 5.00 |
| SHAFT MAXIMUM RADIAL LOAD(N) | | 25.00 |
| LIFE(h) | | 6000 |
| TEMPERATURE RISE:MAX.80°C (MOTOR STANDSTILL;FOR 2PHASE ENERGIZED) | | |
| AMBIENT TEMPERATURE -10°C~50°C[14°F~122°F] | | |
| INSULATION CLASS B 130°C[266°F] | | |

| TYPE OF CONNECTION (EXTERN) | | MOTOR | |
|-----------------------------|---------|-------|---------|
| PIN NO | BIPOLAR | LEADS | WINDING |
| 1 | A — | BLK | A |
| 2 | A\ — | GRN | A\ |
| 3 | B — | RED | B |
| 4 | B\ — | BLU | B\ |

HKT2204-702C1-300B-5E

| Voltage | Output | Resolution |
|---------|--------|------------|
| 5V | A B | 300 CPR |

| Flat Cable | 1 | 2 | 3 | 4 | 5 |
|----------------|----|-----|------|-----|------|
| Voltage Output | 0V | N.C | Ch B | +5V | Ch A |



| | | |
|-------|-----------|-----------|
| APVD | | 8.20.2018 |
| CHKD | | |
| 1.5:1 | DRN | |
| SCALE | SIGNATURE | DATE |

STEPPER MOTOR

11HS12-0674D-PG5-E22-300